

IN THE CLAIMS:

A full listing of the claims, including any amendments made by this paper, follows below:

1. (Currently Amended) A feed grip for being coupled to a slide rod of a slicer comprising:

a gripping plate having a front surface and rear surface, said front surface being shaped to grip a food product, said gripping plate including an attachment portion extending generally outwardly from said rear surface, said attachment portion including a pair of opposed, generally laterally extending feet;

a handle having an opening shaped to releasably receive said attachment portion therein such that said attachment portion can be generally rigidly coupled to said handle, and wherein said ~~attachment portion can~~ handle is configured to be manually decoupled, without the use of tools, from said ~~handle~~ attachment portion by twisting said handle relative to said attachment portion such that said attachment portion and said handle are not generally rigidly coupled; and

a feed arm including a pair of ~~annulus~~ feed arm openings, a first one of said ~~annulus~~ feed arm openings being shaped to ~~be generally located between said handle and said gripping plate~~ receive said attachment portion therethrough, a second one of said ~~annulus~~ feed arm openings being shaped to receive said slide rod of said slicer therethrough.

2. (Previously Presented) The feed grip of claim 1 further comprising a wave washer located between said handle and said feed arm or between said feed arm and said gripping plate such that when said wave washer is compressed said wave washer urges said handle away from said gripping plate and/or said feed arm.

3. (Previously Presented) The feed grip of claim 1 wherein said gripping plate includes a plurality of teeth extending generally forwardly from said front surface.

4. (Previously Presented) The feed grip of claim 3 wherein said plurality of teeth each have a length of between about 8.89 mm and about 10.16 mm (about 0.35 and about 0.40 inches) and have a tip diameter of between about 1.27 mm and about 3.81 mm (about 0.05 inches to about 0.15 inches).

5. (Canceled)

6. (Currently Amended) The feed grip of claim 5 1 wherein said feed arm includes a connecting arm ~~coupled to and~~ extending between both of said ~~annulus~~ feed arm openings.

7. (Original) The feed grip of claim 1 wherein said attachment portion includes a pair of spaced generally parallel legs, each leg being coupled to one of said feet, and wherein said opening of said handle includes a pair of opposed end openings, each end opening being shaped to receive one of said feet therein to couple said feed grip to said handle.

8. (Original) The feed grip of claim 7 wherein each foot extends generally outwardly from the associated leg and includes a curved outer surface.

9. (Original) The feed grip of claim 1 wherein said opening of said handle includes a generally inwardly tapered side wall such that said feet engage said side wall and are urged together when said attachment portion is urged into said opening.

10. (Currently Amended) The feed grip of claim 10 wherein said second one of said ~~annulus~~ feed arm openings is formed as the center opening of a generally annular shape which contributes at least 50% of the weight of said feed grip.

11-15 (Canceled)

16. (Currently Amended) A feed grip for being coupled to a slide rod of a slicer comprising:

a gripping plate having a front surface and rear surface, said front surface being shaped to grip a food product, said gripping plate including an attachment portion extending generally outwardly from said rear surface, said attachment portion including a pair of opposed, generally laterally extending feet;

a generally tube-shaped handle having a central opening shaped to releasably receive said attachment portion therein, said handle having a closed axial end with a continuous outer surface such that said closed axial end lacks any auxiliary openings that communicate with said central opening, wherein said handle is configured to be decoupled from said attachment portion by twisting said handle relative to said attachment portion; and

a feed arm including a pair of ~~annulus~~ feed arm openings, a first one of said ~~annulus~~ feed arm openings being shaped to ~~be generally located between said handle and said gripping plate receive said attachment portion therethrough,~~ a second one of said ~~annulus~~ feed arm openings being shaped to receive said slide rod of said slicer therethrough.

17. (New) The feed grip of claim 1 wherein said handle has a generally continuous outer surface and lacks any auxiliary openings that communicate with said opening of said handle.

18. (New) The feed grip of claim 1 wherein said handle is generally tube-shaped.

19. (New) The feed grip of claim 1 wherein said handle includes a pair of cam surfaces located in said handle opening, each cam surface being located and configured to interact with one of said feet to urge an associated foot inwardly when said handle is twisted relative to said attachment portion.

20. (New) The feed grip of claim 16 wherein said handle has a generally continuous outer surface and lacks any auxiliary openings that communicate with said central opening.

21. (New) The feed grip of claim 16 wherein said handle includes a pair of cam surfaces located in said central opening, each cam surface being located and configured to interact with

one of said feet to urge an associated foot inwardly when said handle is twisted relative to said attachment portion.

22. (New) The feed grip of claim 16 wherein said handle is configured to be manually decoupled, without the use of tools, from said attachment portion by the twisting of said handle relative to said attachment portion such that said attachment portion and said handle are not generally rigidly coupled.

23. (New) A feed grip for being coupled to a slide rod of a slicer comprising:
a gripping plate having a front surface and rear surface, said front surface being shaped to grip a food product;

a handle shaped to be generally rigidly coupled to said gripping plate, and wherein said handle is shaped to be manually decoupled from said gripping plate by twisting said handle relative to said gripping plate such that said gripping plate and said handle are not generally rigidly coupled; and

a feed arm configured to be coupled to at least one of said gripping plate or said handle, wherein said feed arm is configured to receive the slide rod of a slicer therethrough.

24. (New) The feed grip of claim 23 further comprising an attachment structure for coupling said gripping plate and said handle, said attachment structure including a pair of opposed feet and a pair of corresponding end openings shaped and located to receive said feet therein such that when each foot is received in a corresponding end opening said gripping plate and said handle are rigidly coupled together.

25. (New) The feed grip of claim 24 wherein each foot is shaped and configured to be moved out of said corresponding end opening upon said twisting motion to decouple said handle and said gripping plate.

26. (New) The feed grip of claim 25 further comprising a pair of cam surfaces located and configured to interact with one of said feet or with said handle to urge an associated foot out

of said corresponding end opening when said handle is twisted relative to said attachment portion.

27. (New) The feed grip of claim 23 wherein said feed arm includes a pair of feed arm openings, a first one of said feed arm openings being shaped to receive at least part of said gripping plate therethrough, a second one of said feed arm openings being shaped to receive said slide rod of said slicer therethrough.